

SAM SUCTION RANGE

SAM 15 DATA SHEET

SAM suction units are designed to run quietly for long periods of time. At their heart is a state of the art oil-free diaphragm pump combined with multiple safety features including internal filters (hydrophobic) and overflow control valves.

A range of accessories is available including bedside stands, mobile conversion kits, foot switch controls, disposable tubing and curettes, stainless steel cannulae and obstetric suction cups.

SAM 15

INTRA-UTERINE ASPIRATOR

Vacuum	0 to 0.85 bar / 0 to 650 mmHg
Flow rate	30 l/min
Collection Jars	1 x 2 litre
Unit Dimensions	38 x 45 x 20 (H x W x D cm)
Weight	10kg
Noise Level	50dB
Voltage	230v +/- 10%~ 50/60Hz 110v +/- 5%~ 50/60Hz

Complies with Medical Directive 93/42/EEC
BS EN ISO 10079-1
BS EN 60601-1
BS EN 60601-1-2



The SAM 15 aspirator is a top quality surgical suction unit designed to be highly adaptable. It is a high flow, high vacuum unit for intra-uterine procedures and benefits from a single collection jar with a wide bore top complete with specimen filter. Its reputation for reliability and ease of operation has established it among the most widely used units in the medical world today.

As standard, the SAM 15 incorporates an autoclaveable SAM 2 collection vessel fitted with a float valve system, providing automatic shut-off to avoid over-flow. The SAM 15 is also available with a choice of disposable collection systems including Serres, Abbott, VacSax and Pennine. Other disposable collection systems can also be fitted to the SAM 15 on request.